

### Technical Characteristics

Composition	100 % coated glass fiber
Treated fabric weight (average value)	250 g/m <sup>2</sup> = 7,37 oz/yards <sup>2</sup> (± 8 %)
LOI	17%
Emission in indoor air	A+
Oekotex certificate standard 100	Class I
Fire resistance (ASTM E84)	Class A Fire rated

### Recommendation for application

Quantity of glue	250 g/m <sup>2</sup> = 10,55 oz/yards <sup>2</sup>
Quantity of acrylic paint	200-300 g/m <sup>2</sup> = 8,44-12,66 oz/yards <sup>2</sup>

### Dimensions & Packaging

Width (individual value)	100 cm = 39,37 inches (± 1 % or closed pattern repeat)
Roll length (individual value) (1)	15 m = 16,40 yards (± 1 %)
Paintable surface (2)	Outside
Roll packaging (2)	Plastic foil
Label on roll (2)	With installation instructions
# rolls / pallet	66
Storage conditions	Dry room, storing temperature from 14 °F to 122 °F. If product is not processed up to one week, it is not recommended to open a package or to remove a package from a roll.

### Quality Control

Traceability (2)	Lot no. marked on the back side of the roll and on the small sticker on the roll
Defects marked by label (2)	Maximum 3 point defects / 50 m = 50,68 yards
Each defect is balanced by	Adding 50 cm = 19,69 inches / defect (2)
Product is carefully checked before leaving the factory but should also be checked just before applying. Any claim should be accompanied with roll sticker and a sample featuring the defect..	

### General Description

Glass fibers made into a heavy duty non-woven smooth substrate veil, and prepainted. This prepainted product saves one layer of paint during application and 1 day of paint drying time. Requires finish coat of paint after installation when adhesive thoroughly dry. Can be used alone to cover small to medium size cracks and irregular surfaces, or used as a liner under conventional wall coverings. This Renovation product still offers durable protection to walls and ceilings by reinforcing the surfaces; resisting abrasion; providing impact resistance, and covering cracks; and can easily be repainted when time to redecorate. Suitable for residential or commercial projects whether **new construction or renovation**.

(1) Other dimensions or features on request

(2) Details are described in works standard 0337

### Properties

- ° Tear resistant
- ° Easy re-paintable
- ° Prepainted
- ° High tensile strength
- ° Breathable
- ° Fire resistant
- ° Flat finish