

### Technical Characteristics

|                                       |  |
|---------------------------------------|--|
| Composition                           | 100 % coated glass fiber                                 |
| Treated fabric weight (average value) | 190 g/m <sup>2</sup> = 5,6 oz/yards <sup>2</sup> (± 8 %) |
| LOI                                   | 16.7%  |
| Emission in indoor air                | A+   |
| Oekotex certificate standard 100      | Class II   |
| Fire resistance (ASTM E84)            | Class A Fire rated                                       |

### Recommendation for application

|                           |  |
|---------------------------|--|
| Quantity of glue          | 250 g/m <sup>2</sup> = 10,55 oz/yards <sup>2</sup>           |
| Quantity of acrylic paint | 350-500 g/m <sup>2</sup> = 14,77-21,10 oz/yards <sup>2</sup> |

### Dimensions & Packaging

|                                    |   |
|------------------------------------|---|
| Width (individual value)           | 100 cm = 39,37 inches (± 1 % or closed pattern repeat)  |
| Roll length (individual value) (1) | 50 m = 54,68 yards (± 1 %)  |
| Paintable surface (2)              | Outside   |
| Roll packaging (2)                 | Plastic foil  |
| Label on roll (2)                  | With installation instructions  |
| # rolls / pallet                   | 18  |
| Storage conditions                 | Dry room, storing temperature from 14 °F to 122 °F. If product is not processed up to one week, it is not recommended to open a package or to remove a package from a roll. |

### Quality Control

|  |  |
|--|--|
| Traceability (2)   | Lot no. marked on the back side of the roll and on the small sticker on the roll |
| Defects marked by label (2)  | Maximum 3 point defects / 50 m = 50,68 yards                                     |
| Each defect is balanced by   | Adding 50 cm = 19,69 inches / defect (2)   |
| Product is carefully checked before leaving the factory but should also be checked just before applying. Any claim should be accompanied with roll sticker and a sample featuring the defect.. |  |

### General Description

Classic range is glass fiber yarns that are woven into paintable glass textile wallcovering textures. The wall covering is used to cover interior walls and ceilings. This range offers durable protection to walls and ceilings by reinforcing the surfaces; resisting abrasion; providing impact resistance, and covering cracks; and can easily be repainted when time to redecorate. Suitable for residential or commercial projects whether **new construction or renovation**.

(1) Other dimensions or features on request

(2) Details are described in works standard 0337

### Properties

- ° Tear resistant
- ° Fire resistant
- ° Breathable
- ° High tensile strength
- ° Easy re-paintable